

Please add the following new claims:

--2. The architecture of claim 1 wherein said stateless human interface device is accessed by a user using an identifier.--

--3. The architecture of claim 2 wherein said identifier comprises a smart card.--

--4. The architecture of claim 2 wherein said identifier comprises a biometric identifier.--

--5. The architecture of claim 2 wherein said user accesses a computing session of said user when said user accesses said stateless human interface device.--

--6. The architecture of claim 5 further including a plurality of stateless human interface devices coupled across said interconnect fabric to said data source.--

--7. The architecture of claim 6 wherein a user can access said session at any of said plurality of stateless human interface devices by using said identifier.--

--8. The architecture of claim 1 wherein said data source comprises a plurality of data services.--

--9. The architecture of claim 8 wherein output of said plurality of data services is converted to a common protocol for transmitting across said interconnect fabric to said stateless human interface device.--

AJ Sub BA

--10. A computing system comprising:
a centralized processing source providing computation and data generation for a plurality of user sessions;
a plurality of stateless human interface devices coupled through an interconnect fabric to said centralized processing source, wherein each of said stateless human interface devices receive data from said centralized processing source and display output to a user initiating one of said plurality of user sessions, and wherein each of said stateless human interface devices provide user input to said centralized processing source across said interconnect fabric; and
an identifier used by a user at one of said stateless human interface devices which identifies said user such that a session associated with said user is directed through said interconnect fabric to said one of said stateless human interface devices.--

--11. The system of claim 10 wherein a state of a user session is maintained at said centralized computing resource.--

--12. The system of claim 11 wherein said user input comprises keyboard strokes.--

--13. The system of claim 11 wherein said user input comprises cursor movements.--

--14. The system of claim 11 wherein said user input comprises audio.--

--15. The system of claim 11 wherein said user input comprises video.--

--16. The system of claim 11 wherein said user can access said session at any of said plurality of stateless human interface devices by using said physical identifier.--


--17. A computing system comprising:
a plurality of computational service providers;
an interconnect fabric coupled to said computational service providers;
and
a plurality of stateless interface devices coupled to said interconnect fabric.--

--18. The computing system of claim 17 wherein said plurality of computational service providers provide data to said stateless interface devices across said interconnect fabric, and said stateless interface devices display said data.--

--19. The computing system of claim 18 wherein said computational service providers provide data associated with a user session associated with a user.--

--20. The computing system of claim 19 wherein said user accesses said user session at any of said plurality of stateless interface devices.--

--21. The computing system of claim 20 wherein said user accesses said user session at one of said stateless interface devices by presenting an identifier to said one of said stateless interface devices.--

--22. The computing system of claim 21 wherein said plurality of computational service providers include a first member and a second member and wherein said first member specializes in computing a first type of data and said second member specializes in computing a second type of data.

--23. The computing system of claim 22 wherein said first member provides said first type of data to said stateless interface device and said second member provides said second type of data to said stateless interface device.--

--24. The computing system of claim 23 wherein said identifier comprises a password.--

--25. The computing system of claim 23 wherein said identifier comprises a smart card.--

--26. The computing system of claim 23 wherein said identifier comprises a biometric identifier.--

--27. The computing system of claim 23 wherein said user can interrupt said user session at one of said interface devices and resume said user session at another of said interface devices.--

*Sub
p4*
AB
--28. A method of computing comprising the steps of:
providing a plurality of computational service providers;
coupling said computational service providers to an interconnect fabric;
coupling a stateless interface device to said interconnect fabric; and
providing data to said stateless interface device from said computational service providers across said interconnect fabric.--

--29. The method of claim 28 further including the step of generating a user session with said computational service providers.--

--30. The method of claim 29 further including the step of accessing said user session by presenting an identifier at said stateless interface device.--

--31. The method of claim 30 wherein said session is transmitted to said stateless interface device when said identifier is presented.--

--32. The method of claim 31 wherein said identifier comprises a smart card.--

--33. The method of claim 31 wherein said identifier comprises a password.--

--34. The method of claim 31 wherein said identifier comprises a biometric identifier.--

--35. The method of claim 31 further including a plurality of stateless interface devices coupled to said interconnect fabric.--

--36. The method of claim 31 further including the step of interrupting said user session at one of said interface devices and resuming said user session at another of said interface devices.--

--37. The method of claim 28 wherein said computational service providers receive said data from an outside source.--

--38. The method of claim 37 wherein said outside source is the Internet.

--39. The method of claim 37 wherein said outside source is a broadcast entity.--

--40. The method of claim 39 wherein said broadcast entity transmits a television signal.--

--41. The method of claim 39 wherein said broadcast entity transmits a radio signal.--

--42. The method of claim 28 wherein said step of providing data to said stateless interface device comprises:

said plurality of computational service providers transforming
disparate output to a common protocol for transmitting across said
interconnect fabric to said stateless interface device.--

*Sub
BE*
--43. A method of computing comprising the steps of:
providing a plurality of computational service providers;
coupling said computational service providers to an interconnect
fabric;
coupling a stateless interface device to said interconnect fabric;
initiating a session by a user on said stateless interface device;
providing input to said stateless interface device;
transmitting said input across said interconnection fabric to one or
more of said plurality of computational service providers;
operating on said data by said one or more of said plurality of
computational service providers to produce modified data wherein said step
of operating includes changing state and performing computations;
providing said modified data to said stateless interface device from said
computational service providers across said interconnect fabric; and
displaying said data on said stateless interface device.--

--44. A method of computing comprising the steps of:
providing an interconnect fabric;
providing a plurality of computational service providers coupled to
said interconnect fabric;
providing a proxy service coupled to said interconnect fabric wherein
data is transmitted from said plurality of computational service providers to
said proxy service across said interconnect fabric; and

providing a stateless interface device coupled to said interconnect fabric wherein data is transmitted from said proxy service to said stateless interface device across said interconnect fabric. --

--45. The method of claim 44 wherein said plurality of computational service providers access one or more databases.--

--46. The method of claim 45 wherein said proxy service is configured to generate a query upon said one or more databases.--

*Int
B4* --47. A method of computing comprising:
a plurality of state machines;
a stateless machine;
an interconnect fabric coupling said plurality of state machines to said stateless machine;
providing input to said stateless machine;
transmitting said input to one or more of said plurality of state machines;
operating on said input by said one or more of said plurality of state machines to produce output;
transmitting said output to said stateless machine; and
displaying said output on said stateless machine.--

--48. The method of claim 47 wherein before said input and said output are transmitted, said input and said output are transformed to a protocol readable by said stateless machine.--